


Small Signal Schottky Diode


SOD123

Features

- Epoxy meets UL-94 V-0 flammability rating and halogen free
- Moisture Sensitivity Level 1
- V_{RRM} 40V/30V/20V
- I_{FAV} 0.35A
- Part no. with suffix "Q" means AEC-Q101 qualified

Applications

- For general purpose applications
- Automotive

Mechanical Data

- **Case:** SOD123
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

■ Maximum Ratings ($T_a=25^{\circ}\text{C}$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	CONDITIONS	VALUE	
Repetitive peak reverse voltage	V_{RRM}	V		SD103AWQ	40
				SD103BWQ	30
				SD103CWQ	20
Average Forward Current	I_{FAV}	A		0.35	
Peak Forward Surge Current	I_{FSM}	A	8.3ms, half sine	3	
Power Dissipation	P_{tot}	mW		400	
Thermal Resistance Junction to Ambient	R_{thJA}	K/W		250	
Junction Temperature	T_J	$^{\circ}\text{C}$		-55 to +125	
Storage Temperature Range	T_{stg}	$^{\circ}\text{C}$		-55 to +150	



SD103AWQ / SD103BWQ / SD103CWQ

■ Electrical Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	CONDITIONS	PART	MIN	MAX
Forward Voltage	V _F	V	I _F =20mA			0.37
			I _F =200mA			0.6
Reverse Leakage Current	I _R	uA	V _R =30V	SD103AWQ		5
			V _R =20V	SD103BWQ		5
			V _R =10V	SD103CWQ		5
Reverse Breakdown Voltage	V _{BR}	V	I _R =100uA	SD103AWQ	40	
				SD103BWQ	30	
				SD103CWQ	20	
Junction Capacitance	C _J	pF	V _R =0V, f =1MHz			50
Reverse Recovery Time	t _{rr}	ns	I _F =I _R =10mA, I _{rr} =1mA, R _L =100Ω			7

■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
SD103AWQ SD103BWQ SD103CWQ	F2	Approximate 0.010	3000	30000	120000	7" reel



■ Characteristics (Typical)

Fig.1: P_D-T_A




Fig.2: Capacitance Characteristics




Fig.3: Forward Characteristics






Fig.4: Reverse Characteristics






SD103AWQ / SD103BWQ / SD103CWQ

■ Outline Dimensions



DIMENSIONS				
DIM	INCHES		MM	
	MIN	MAX	MIN	MAX
A	0.140	0.152	3.550	3.850
B	0.100	0.112	2.550	2.850
C	0.055	0.071	1.400	1.800
D	0.037	0.053	0.950	1.350
E	0.020	0.028	0.510	0.710
G	0.006	0.018	0.150	0.450
H	0.003	0.010	0.080	0.250
J	0.000	0.006	0.000	0.150
θ	0	8°	0	8°

■ Marking Information



	Marking
SD103AWQ	S4
SD103BWQ	S5
SD103CWQ	S6

Note:

1. All marking is at middle of the product body
2. All marking is in laser marking
3. XX. is Marking Code
4. Body color: Black



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, life-saving, life-sustaining, or military, Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.